

Model BY301G15F

File Number: E531449

Yellow Card®



COMPANY

Guangdong Beiyan New Material Technology Co., Ltd  
Room 601, Building 1, No. 770, Xiecao Road, Xiegang Town,  
Dongguan, Guangdong Sheng 523000 China

MODEL INFO


BY301G15F  
Polybutylene Terephthalate (PBT), furnished as pellets

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
0.8 mm, Color: NC, BK	V-0	
3.0 mm, Color: NC, BK	V-0	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
0.8 mm, Color: NC, BK	V-0	
3.0 mm, Color: NC, BK	V-0	
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
0.8 mm	PLC 3	
3.0 mm	PLC 0	
High Amp Arc Ignition (HAI)		UL 746A
0.8 mm	PLC 0	
3.0 mm	PLC 0	

Feedback

THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
0.8 mm	75 °C	
3.0 mm	75 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
0.8 mm	75 °C	
3.0 mm	75 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
0.8 mm	75 °C	
3.0 mm	75 °C	

Report Date: 2023-05-20  
Revision Date: 2023-05-22



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."